

**PROGRESS IN CHEMICAL TREATMENT OF LEU TARGETS
BY THE MODIFIED CINTICHEM PROCESS***

D. Wu and S. Landsberger
University of Illinois at Urbana-Champaign
103 South Goodwin Avenue
Urbana, Illinois 61801
U.S.A.

G. F. Vandegrift
Argonne National Laboratory
Chemical Technology Division
9700 South Cass Avenue
Argonne, Illinois 60439
U.S.A

Presented at the
1996 International Meeting on
Reduced Enrichment for Research and Test Reactors

October 7-10, 1996
Seoul, Korea.

The submitted manuscript has been authored by a contractor of the U. S. Government under contract No. W-31-109-ENG-38. Accordingly, the U. S. Government retains a nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or allow others to do so, for U. S. Government purposes.

*Work supported by the U.S. Department of Energy
Office of Nonproliferation and National Security
under Contract W-31-109-Eng-38

PROGRESS IN CHEMICAL TREATMENT OF LEU TARGETS BY THE MODIFIED CINTICHEM PROCESS

D. Wu and S. Landsberger
University of Illinois at Urbana-Champaign
Urbana, Illinois USA

G. F. Vandegrift
Argonne National Laboratory
Argonne, Illinois USA

ABSTRACT

Presented here are recent experimental results on tests of a modified Cintichem process for producing ^{99}Mo from low enriched uranium (LEU). Studies were focused in three areas: (1) testing the effects on ^{99}Mo recovery and purity of dissolving LEU foil in nitric acid alone, rather than in the sulfuric/nitric acid mixture currently used, (2) measuring decontamination factors for radionuclide impurities in each purification step, and (3) testing the effects on processing of adding barrier materials to the LEU metal-foil target. The experimental results show that switching from dissolving the target in the sulfuric/nitric mixture to using nitric acid alone should cause no significant difference in ^{99}Mo product yield or purity. Further, the results show that overall decontamination factors for gamma emitters in the LEU-target processing are high enough to meet the purity requirements for the ^{99}Mo product. The results also show that the selected barrier materials, Cu, Fe, and Ni, do not interfere with ^{99}Mo recovery and can be removed during chemical processing of the LEU target.

INTRODUCTION

The Cintichem process for producing ^{99}Mo currently uses high enriched uranium (HEU, ~93% ^{235}U) as irradiated UO_2 deposited on the inside of a cylindrical target [1, 2]. In order to convert the process to low enriched uranium (LEU, < 20% ^{235}U) as a uranium metal-foil target, effects of modifying the dissolver solution due to this conversion must be studied, and necessary modifications to processing must be developed. In the Cintichem process, the UO_2 in the target is dissolved in a mixture of sulfuric and nitric acid. After the target is dissolved, the solution is prepared (by the addition of several reagents) for molybdenum precipitation with *o*-benzoin oxime. Following precipitation, the precipitate is collected, washed, and redissolved. The redissolved molybdenum solution is then passed through two additional purification steps. It is our objective in switching to LEU to maintain the process for molybdenum recovery and separation from uranium (and its fission and absorption products) as close as possible to the current Cintichem process. It is also our goal to make improvements to the process that will alleviate any economic detriment to conversion to LEU.

Argonne National Laboratory and the University of Illinois at Urbana-Champaign are collaborating with the National Atomic Energy Agency (BATAN) of Indonesia to develop and demonstrate the use of LEU targets in the Cintichem process. This work is a follow-up to work on this project reported last year [3-6]. In the next few months, we plan to perform the demonstration of processing a fully irradiated LEU metal foil at the PUSPIPTEK Radioisotope Production Center in Serpong, Indonesia. During 1996, we focused on three technical areas: (1) testing the effects on ^{99}Mo recovery and purity of dissolving the LEU foil in nitric acid alone rather than in the sulfuric/nitric acid mixture currently used, (2) measuring decontamination factors for radionuclide impurities in

each purification step, and (3) testing the effects on processing of adding barrier materials to the LEU metal-foil target. The results of these studies are reported below.

NITRIC ACID ALONE AS DISSOLVER SOLUTION

The primary consideration for converting the dissolver solution to nitric acid alone is facilitating waste treatment and disposal. Sulfate in the acidic waste solution from the ^{99}Mo recovery step complicates uranium recovery, waste volume reduction, and waste disposal [7]. Therefore, removal of sulfuric acid from the dissolver solution is likely to significantly reduce total processing costs. A series of experiments was performed to measure the molybdenum recovery efficiency and radioisotope decontamination over a range of nitric acid concentrations. Results were compared to earlier data for the mixed-acid dissolver solution.

Precipitation of Mo(VI) by β -benzoin oxime (β -BO) is a standard analytical method for molybdenum. The standard procedure requires molybdenum in 1M sulfuric acid [8-10]. Molybdenum precipitation is quantitative, and the precipitate contains very little impurities. In our previous tests, we found that molybdenum can be also precipitated quantitatively with β -benzoin oxime from a nitric acid solution [3,4]. However, to prove the feasibility of using the nitric acid alone as a dissolver solution, we had to verify that radionuclide decontamination of the ^{99}Mo product is not degraded by this modification. Four irradiated-LEU-tracer and several ^{99}Mo -tracer experiments were also run for determining the effects of the nitric acid concentration of the dissolver solution.

Table 1 compares the results of LEU tracer experiments using nitric-acid-alone dissolver solutions and the results for sulfuric/nitric mixtures reported last year [4]. The compositions of the simulated nitric-acid dissolver solutions were (1) 0.7M nitric acid and 1.7M uranium, (2) 5M nitric acid with 0.7M uranium, (3) 0.8M nitric acid and 0.8M uranium, and (4) 0.7M nitric acid and 1.8M uranium. To each solution was added a small volume of an irradiated solution of ~10 mg/mL LEU in 0.3M HNO_3 and 0.2M H_2SO_4 . Within the nitric acid data, no trend was evident for differences in radioisotope decontamination with solution composition. Where different values were measured for the four nitric acid experiments, a range was reported. When detection limits were all that could be measured, the lowest detection limit was reported. As can be seen from the comparison in Table 1, there is no significant effect of eliminating sulfuric acid for either molybdenum recovery or radioisotope decontamination. As reported in the past [3-5], most of the decontamination is done in the precipitation of molybdenum with β -BO, and the following purifications are polishing steps. We must note that our tracer tests only indicate chemical behavior; verification of this behavior will require full-scale demonstrations using fully irradiated uranium-foil targets.

Other experiments were performed to measure molybdenum recovery as a function of uranium and nitric acid concentrations (see Table 2). The experiments included solutions prepared from dissolving depleted uranium foil in nitric acid (#1 and 2), UO_2 in nitric acid (#3), uranyl nitrate dissolved in nitric acid (#4 and 5) or sulfuric acid (#6), and nitric acid solution with no uranium (#7). The results validate the results reported last year [3] that molybdenum recovery efficiency is high under a variety of conditions. Again, we see no loss of ^{99}Mo yield by dissolving targets in nitric acid alone.

Table 1. Comparison of Impurity Levels after Each Purification Step of the Cintichem Processing of Simulated LEU Targets Dissolved in Either Nitric Acid Alone or the Standard Sulfuric/Nitric-Acid Cocktail Solution

Nuclide	Impurity Levels, $\mu\text{Ci}/\text{mCi-}^{99}\text{Mo}$					
	-BO Precipitation		Purification 1		Purification 2	
	Nitric Alone ^a	Mixture	Nitric Alone	Mixture	Nitric Alone	Mixture
Ba-140	0.03	0.07	<0.38	<0.17	<0.42	<0.13
Ce-141	<0.12	<0.04	<0.11	<0.03	<0.12	<0.02
Ce-143	<0.3	0.41	<0.15	<0.21	<0.17	<0.20
I-131	1.6-2.4	2.35	<3.25	<0.58	<3.60	<0.32
Te/I-132	0.22-0.44	0.56	<0.55	<0.08	<0.62	<0.09
I-133	6.7-15.6	27.99	1.16	1.64	0.92	1.25
I-135	4.0-8.5	18.88	0.59	0.71	0.42	0.48
La-140	<0.04	0.43	<0.01	0.18	<0.01	<0.15
Nb-95	0.47-1.3	0.80	0.23	<0.18	<0.04	<0.02
Zr/Nb-97	5.5-274	24.79	14.57	34.65	<0.08	5.53
Nd-147	<0.6	0.10	<0.20	<0.16	<0.25	<0.09
Np-239	<0.74	<0.74	<0.33	<0.49	<0.38	<0.47
Pm-151	<0.54	<0.54	<0.26	<0.38	<0.29	<0.37
Rh-105	<0.55	<0.55	<0.26	<0.38	<0.28	<0.38
Ru-103	0.43-1.02	0.50	0.05	<0.04	0.03	<0.02
Sb-127	<0.10	<0.24	<0.15	<0.25	<0.17	<0.26
Sr-91	<0.36	0.32	<0.20	<0.34	<0.26	<0.33
Sr-92	<0.04	n.m. ^b	<0.02	n.m. ^b	<0.02	n.m. ^b
Y-93	<3.70	<2.27	<0.88	<1.26	<1.10	<1.19
Zr-95	0.2-5.9	0.66	<0.08	0.59	<0.09	0.52
	⁹⁹ Mo Recovery, %					
Mo-99	94.8-98.0	98.3	95.2	96.5	93.2	91.3

^aRange of results of four separate tests with different nitric acid and uranium concentrations. When two or more of the results were below detection limits (< values), the lowest detection limit is presented

^bn.m.: not measured in the experiment.

Table 2. Molybdenum Recovery by -Benzoin Oxime Precipitations from Various Acidic Uranyl Nitrate Solutions

Solution No. ^a	Concentration, <u>M</u>				Mo Recovery, %
	H ⁺	NO ₃ ⁻	SO ₄ ²⁻	UO ₂ ²⁺	
1	0.75	2.35	0	0.8	100±3
2	5.0	6.5	0	0.75	93±3
3	0.4	4.0	0	1.8	100±3
4	0.75	4.35	0	1.8	94±3
5	0.75	2.75	0	1.0	100±3
6	1.5	2.0	0.75	1.0	100±3
7	0.75	0.75	0	0	100±3

^aSee text for description of how solutions were prepared.

DECONTAMINATION OF THE ⁹⁹MO FROM OTHER RADIOISOTOPES

The allowed radiochemical impurity levels in ⁹⁹Mo product are very low, ranging from 0.1 to 10⁻⁷ μCi/mCi-⁹⁹Mo. Therefore, each purification step must work effectively. The gamma-emitting isotopes that need to be analyzed in the ⁹⁹Mo product are tabulated in Table 3. By using ORIGEN2, we calculated the activities of these radioisotopes in an 18-gram LEU target at 24 hours after discharge from the Indonesian RGS-GAS reactor, following a 120-hour irradiation at full power (second column of Table 3). Columns 3 through 5 contain decontamination factors we measured in our tracer experiments for each processing step. The Cintichem process uses three purification steps: the -BO precipitation and two polishing steps (purifications 1 and 2). The predicted impurity levels in units of μCi/mCi-⁹⁹Mo in the irradiated LEU target are listed in the last column. The calculations show that, except for ¹⁰³Ru, radioisotopic decontamination levels can be met easily. Because ¹⁰³Ru contamination is not a concern in the current Cintichem product from HEU targets and because substitution of LEU will not affect the fission yield, this result for ¹⁰³Ru may indicate a limitation of tracer experiments more than a problem with LEU substitution.

Table 3. Calculated Impurity Levels of a Fully Irradiated LEU Target and the ⁹⁹Mo Product^a

Nuclide	Calculated Target Activity, Ci	Measured Decontamination Factors ^b			Calculated Product Impurity Level, μCi/mCi- ⁹⁹ Mo
		Precipitation	Purification 1	Purification 2	
Ba-140	292	>516	>162	>165	<3.6E-05
Ce-141	121	>1116	328	419	<1.3E-06
Ce-143	685	>3354	313	641	<1.7E-06
I-131	186	51	28	41	5.3E-03
I-133	628	91	35	51	6.3E-03
I-135	104	121	38	43	8.8E-04
La-140	224	>2409	>104	>149	<1.0E-05
Mo-99	697	1.04	1.05	1.08	-
Nb-95	4.7	4	>13	>9.5	<1.7E-02
Nb-97	480	11	56	1410	9.2E-04
Nd-147	119	208	>62	>59	<2.6E-04
Np-239	1610	>1770	>247	>333	<1.9E-05
Pm-151	45	103	>16	>21	<2.1E-03
Rh-105	102	>276	>34	>46	<4.0E-04
Ru-103	54	113	1.3	3.7	1.7E-01
Sb-127	13.6	>41	1.3	>10	<4.3E-02
Sr-89	65.7	-	-	-	<2.3E-07 ^c
Sr-90	0.39	-	-	-	<1.4E-09 ^c
Sr-91	209	>3452	235	>586	<7.4E-07
Sr-92	2.65	>2101	>71	>63	<4.7E-07
Te/I-132	464	>5083	327	657	<7.1E-07
Y-93	258	>1294	511	822	<8.0E-07
Zr-95	70	13	27	>49	<6.8E-03
Zr-97	447	17	23	>41	<4.6E-02

^aBasis is an 18-g LEU target, 24 hours after discharge from the RGS-GAS reactor, following a 120-hour irradiation at full power.

^bRatio of activity in the molybdenum solution before and after treatment.

^cPredicted from Sr-91 behavior.

EFFECTS OF BARRIER MATERIALS ON PROCESSING

Development of LEU metal-foil targets has led to the use of thin (10 μm) metal barriers between the uranium foil and the target walls [11]. Three metals (Cu, Fe, and Ni) were selected as primary candidates for the barrier material based on the basis of their physical, chemical, and nuclear properties. Physical characteristics are important to target fabrication and are discussed in reference 10. Important chemical characteristics are foil dissolution (reported in reference 12) and the effect of barrier materials on the recovery and purity of ^{99}Mo (discussed below). The nuclear properties of interest are the radioisotopes generated in the barrier during target irradiation and their activity levels, which must be removed from molybdenum during processing, as discussed below.

Table 4 shows ORIGEN2 calculations for the radioisotopes generated in Fe, Ni, and Cu barriers during LEU target irradiations in the RGS-GAS reactor. The target contains an 18-g uranium-metal foil with a 10- μm metal barrier on each side of the foil. The results of these calculations show that only a copper barrier would generate enough radioactivity to be of concern. For ^{64}Cu to be less than 0.1 $\mu\text{Ci/mCi-}^{99}\text{Mo}$ in the molybdenum product, its overall decontamination factor must be $>3,100$.

Neither the barrier materials nor their neutron-activation products are reported to interfere with the precipitation of molybdenum by $-\text{BO}$ [8-10]. Experiments were run to verify the noninterference of these metal ions by using solutions prepared to simulate dissolving the barrier-clad uranium foil in nitric acid. In the same experiments, we measured the amount of each barrier metal that carried with the molybdenum precipitate. Table 5 shows the results of these experiments. The molybdenum recovery was high for all experiments, as were the measured decontamination factors. It is likely that the differences in the decontamination factors are more an indication of how well the precipitate was washed in each experiment rather than chemical differences in the barrier-metal ions.

Table 4. Radioisotopes Generated from Barrier Metals during Irradiation of an LEU Metal Targets^a

Metal	Isotope	Half-Life	Activity, mCi
Fe	Fe-55	2.73 y	37
	Fe-59	44.5 d	26
	Mn-54	312 d	1.3
	Mn-56	2.56 h	1.0
Ni	Ni-65	2.52 h	53
	Co-58	70.92 d	97
Cu	Cu-64	12.7 h	153,000
	Cu-67	61.9 h	0.6

^aBarrier material (10 μm) on both sides of an 18-g metal foil irradiated in the RGS-GAS reactor at full power for 120 hours.

Table 5. Effects of Barrier Materials on γ -BO Precipitation: Molybdenum Yield and Barrier-Metal Decontamination Factors^a

	Cu	Fe	Ni
Molybdenum recovery (%)	99 ± 3	96 ± 3	96 ± 3
Decontamination factors	1680	258	660

^aSolution contained 0.75M HNO₃, 1.5M UO₂(NO₃)₂, and the concentration of Cu, Ni, or Fe corresponding to a 10- μ m barrier on either side of the uranium foil.

The decontamination factors measured for iron and nickel are more than high enough to meet impurity requirements for the molybdenum product. However, the removal of ⁶⁴Cu may require additional decontamination. For this reason, we tested the removal of copper by the two polishing steps; these tests showed that the overall decontamination factor for the two polishing steps should be >10,000. A combination of all three steps should therefore effectively reduce ⁶⁴Cu contamination to well below concern.

CONCLUSION

Testing and development activities are continuing at Argonne National Laboratory and the University of Illinois at Urbana/Champaign to support modification of the Cintichem process for use with LEU targets and to assist BATAN researchers at the PUSPIPTEK Radioisotope Production Center, who are preparing to demonstrate this process on a fully irradiated LEU target. Our collaboration with BATAN is vital to developing and validating this process. Results this year have added to the database showing that substitution of LEU in the Cintichem process will be successful and advanced our progress toward the full-scale demonstration to be done by BATAN.

Our experimental results predict that replacing the current dissolution cocktail, which contains both nitric and sulfuric acids, with nitric acid alone will not compromise the effectiveness of the Cintichem process. In our tracer experiments with this substitution, molybdenum recovery and purity were not degraded. Removal of sulfuric acid from the dissolver solution will decrease waste treatment and disposal costs and increase the stability of the disposed waste form. On the basis of measured decontamination factors from our tracer experiments, molybdenum produced from processing fully irradiated LEU targets is predicted to meet radiochemical purity limits. Its yield will be equivalent to that currently produced from HEU. Likewise, addition of barrier materials will not affect the process. A full-scale demonstration of process will take place in the near future at PUSPIPTEK.

FUTURE WORK

Future activities will be aimed at supporting the full-scale demonstrations to be performed in Indonesia.

REFERENCES

- [1] H. Arino, H. H. Kramer, J. J. McGovern, A. K. Thornton, "Production of High Purity Fission Product Molybdenum-99," U.S. Patent 3,799,883 (1974).
- [2] H. Arino, F. J. Cosolito, K. D. George, A. K. Thornton, "Preparation of a Primary Target for the Production of Fission Products in a Nuclear Reactor," U.S. Patent 3,940,318 (1976).
- [3] D. Wu, B. A. Buchholz, S. Landsberger, and G. F. Vandegrift, "Processing of LEU Targets for Mo Production—Testing and Modification of the Cintichem Process," Proceedings of the XVIII International Reduced Enrichment for Research and Testing Reactors Meeting, Paris, France, September 17-21, 1995, paper no. 3-3 (May 1996).
- [4] D. Wu, S. Landsberger, and G. F. Vandegrift, "Application of Neutron Activation Analysis in a Fission Molybdenum Separation Study," J. Radioanal. Nucl. Chem., in press, 1996.

- [5] Z. Aliludin, A. Mutalib, A. Sukmana, Kadarisman, A. H. Gunwan, G. F. Vandegrift, B. Srinivasan, J. L. Snelgrove, and D. Wu, "Processing of LEU Targets for ^{99}Mo Production—Demonstration of a Modified Cintichem Process," Proceedings of the XVIII International Reduced Enrichment for Research and Testing Reactors Meeting, Paris, France, September 17-21, 1995, paper no. 3-4 (May 1996).
- [6] B. Srinivasan, R. A. Leonard, S. Aase, G. F. Vandegrift, Moeridun, A. A. Rauf, H. Lubis, A. Hardi, S. Amini, and Y. Nampira, "Processing of LEU Targets for ^{99}Mo Production—Dissolution of Metal Foils by Nitric-Acid/Sulfuric-Acid Mixtures," Proceedings of the XVIII International Reduced Enrichment for Research and Testing Reactors Meeting, Paris, France, September 17-21, 1995, paper no. 3-2 (May 1996).
- [7] E. P. Gause, L. G. Stang, D. R. Dougherty, E. Veakis, and J. Smalley "Characterization of the Radioactive Large Quantity Waste Package of the Union Carbide Corporation," BNL-NUREG-30247R Nuclear Waste Management Division, Department of Nuclear Energy, Brookhaven National Laboratory Informal Report, Upton, New York (July 1982).
- [8] A. Elwell, Analytical Chemistry of Molybdenum and Tungsten, Pergamon Press, Oxford, New York, 1977, pp. 40-41.
- [9] A. Parker, Analytical Chemistry of Molybdenum, Springer-Verlag, Berlin, New York, 1983, pp. 146-147.
- [10] A. I. Busev, Analytical Chemistry of Molybdenum (translated by J. Schmorak), Ann Arbor, Humphrey Science Publishers, 1969, pp. 30-31.
- [11] G. L. Hofman, T. C. Wiencek, E. L. Wood, J. L. Snelgrove, A. Suropto, H. Nasution, D. Lufti-Amin, and A. Coogo, "Irradiation Tests of ^{99}Mo Isotope Production Targets Employing Uranium Metal Foils," XIX International Enrichment for Research and Testing Reactors Meeting, Seoul, 6-10 October 1996.
- [12] R. A. Leonard, L. Chen, C. Mertz, and G. F. Vandegrift, "Progress in Dissolving Modified LEU Cintichem Targets," XIX International Enrichment for Research and Testing Reactors Meeting, Seoul, 6-10 October 1996.